

DEKS OLJE



High Quality Wood Care System

Beautiful Woodwork With Minimum Maintenance



- **Coverage:** D1 1-4m² per litre
D2 15m² per litre
- **Recoating:** D1 – Wet on Wet. D2 – 12 hours
D1 with D2 – 3 Days
- **Drying Time:** D1 – 24 hours, D2 – 24 hours
- **Sizes:** 1ltr, 2.5ltr, 20ltr
- **Application:** Brush, Roller



Deks Olje D1 and D2
applied to a hardwood door

Deks Olje pronounced “Deks Olya” is a varnish-like system with a proven track record in the marine environment for over 50 years. Consisting of 2 elements, D1 & D2, Deks Olje will give long life protection to both Soft and Hardwoods while enhancing the woods natural beauty.

The beauty of wood is largely due to the fact that it was once a living, natural material. Once felled, the natural oils in the timber dry out, a process not prevented by coating with a surface only treatment. The Deks Olje system is different in that it penetrates to the heart of the wood.

Deks Olje D1 is the special oil that saturates the wood, literally feeding it with oil to replace those lost. Driving out moisture and air, filling the woods pores with oil, it enriches and stabilises to provide lasting protection to interior and exterior timber.

Deks Olje D2 is the finish coat that is applied to wood treated with D1 for a high gloss finish. D2 provides a tough, flexible and durable surface that is easy to maintain. Easy to apply, the more coats of D2 that are applied the higher the gloss finish and there is no need to sand between coats. Unlike traditional varnishes D2 will not craze or blister and because of D1’s penetrating qualities will not peel or flake as water is unable to get into the wood where it can also cause unsightly stains.

Deks Olje is suitable for all wood types, interior or exterior, new or old

Prevents Flaking
Easy Maintenance
Excellent Traditional Finish

No Blistering or Crazing
Long lasting Protection
Proven Marine Product

Igoe International Ltd. Unit 12, Enterprise Centre, 25 Greenhill Crescent, Watford. WD18 8XU

Tel: 08450 618899 Fax: +44 (0) 1923 219144

Email: sales@igoeinternational.com Website: www.igoeinternational.com : www.owatrol.uk.com

Copyright 2004 © Designed & Developed by the Author, Thomas Rathbone. This leaflet is protected under the terms of license issued by the Copyright Licensing Agency and may not be reproduced in any form without prior permission of the author or company 14/02/08